



Prod. Ref.	37610-N00
Safety cat.	S7S CI LG SC FO SR
Range of sizes	40 - 48 (6,5 - 13)
Weight (sz. 8)	650 g
Shape	B
Width	11

Description: Black water repellent Pull-Up Nubuck ankle boot, **GORE-TEX Performance Comfort Footwear** membrane lining, antistatic, antistatic, anti-shock, slipping resistant, with non metallic **APT PLUS** midsole - type **PS** with Ø 3,0 mm nail.

Plus: METAL FREE. FOOT-PAD footbed, extremely soft and comfortable footbed. Thanks to the very low density polyurethane, the footbed is self-molding granting a right distribution of the body weight and providing an immediate feeling of comfort. High shock absorption is provided from highly resilient material and a perfect cushion in the central area of the heel. **ANTI TORSION SUPPORT** made of polycarbonate and fibreglass conveniently placed between heel and sole, which provides support and protection of the plantar arch, thus preventing harmful bendings and/or unwilling torsion. Perfumed sole. Footwear equipped with a particularly abrasion-resistant material on the toe area (**SC**). Sole design especially conceived for safer standing on ladder rungs (**LG**).

Suggested uses: Construction, maintenance, industries. Footwear for wet environments

Care and maintenance: Clean after each use and dry off away from direct heat. Avoid contact with aggressive chemicals or extreme temperature. Avoid immersion in sea water, lime water or cement mixed with water

MATERIALS / ACCESSORIES

SAFETY TECHNICAL SPECIFICATIONS

		Clause EN ISO 20345:2022+ A1:2024	Description	Unit	Cofra result	Requirement
Complete shoe	Water resistance	5.15.1	Water resistance (area of water penetration after 1000 paces in a surface flooded with water)	cm ²	≤ 3	≤ 3
	Toe cap: non metallic FIBERGLASS toe cap, impact resistant until 200 J and compression resistant until 1500 kg	5.3.2.6	Shock resistance (clearance after shock)	mm	18	≥ 14
		5.3.2.7	Compression resistance (clearance after compression)	mm	14,5	≥ 14
	Anti perforation midsole: in multi-layers highly tensile fabric, penetration resistant, Zero Perforation	6.2.1.1.4	Penetration resistance (PS requirement with Ø 3,0 mm nail)	N	1313	≥ 1100
	Antistatic shoe: the bottom is fit for the dissipation of electrostatic charges	6.2.2.2	Electric resistance			
			- wet	MΩ	51	≥ 0.1
		- dry	MΩ	134	≤ 1000	
	Cold insulation	6.2.3.2	Cold insulation (temp. decrease after 30' C at -17 °C)	°C	6,5	≤ 10
	Energy absorption system	6.2.4	Shock absorption	J	33	≥ 20
	Upper	Black water repellent Pull-Up Nubuck thickness 1,8/2,0 mm	5.4.6	Water vapour permeability	mg/cmq h	> 5,7
			Permeability coefficient	mg/cmq	> 50,3	≥ 15
		6.3	Water absorption		12%	≤ 30%
Quarter lining	GORE-TEX membrane, breathable and abrasion resistant, colour grey thickness 1.2 mm	5.5.4	Water vapour permeability	mg/cmq h	> 10,3	≥ 2
			Permeability coefficient	mg/cmq	> 85,4	≥ 20
	Sole	5.8.4	Abrasion resistance (lost volume)	mm ³	102	≤ 150
		5.8.5	Flexing resistance (cut increase)	mm	0,9	≤ 4
		5.8.7	Interlayer bond strength	N/mm	3,7	≥ 3
	6.4.2	Hydrocarbons resistance (ΔV = volume increase)	%	2,2	≤ 12	
Adherence coefficient of the sole (Slip resistance)	5.3.5.2	ceramic + detergent solution – forepart (contact angle 7°)		0,41	≥ 0,36	

6.2.10	ceramic + detergent solution – heel (contact angle 7°)	0,42	≥ 0,31
	SR : ceramic + glycerol – forepart (contact angle 7°)	0,25	≥ 0,22
	SR : ceramic + glycerol – heel (contact angle 7°)	0,28	≥ 0,19