



Prod. Ref.	37501-N00
Safety cat.	S3S SC LG FO SR
Range of sizes	36 - 48 (3 - 13)
Weight (sz. 8)	560 g
Shape	A
Widht (3 - 6)	10
Widht (6,5 - 13)	11

Description: Black/dark grey **TECHSHELL**, innovative, very tough, abrasion resistant, water repellent and breathable fabric shoe, **SANY-DRY**[®] lining, anti-shock, slipping resistant, with non metallic **APT PLUS** midsole - type **PS** with Ø 3,0 mm nail.

Plus: METAL FREE. High electrical conductivity. Stability of the conductive capability for extended period. **FOOT-PAD ESD** extremely soft and comfortable footbed, **with low electric resistance**. Thanks to the very low density polyurethane, the footbed is self-molding granting a right distribution of the body weight and providing an immediate feeling of comfort. High shock absorption is provided from highly resilient material and a perfect cushion in the central area of the heel. **ANTI TORSION SUPPORT** made of polycarbonate and fibreglass conveniently placed between heel and sole, which provides support and protection of the plantar arch, thus preventing harmful bendings and/or unwilling torsion. Perfumed sole. **TPU insert in the heel**. Footwear equipped with a particularly abrasion-resistant material on the toe area (**SC**). Sole design especially conceived for safer standing on ladder rungs (**LG**).

Suggested uses: Footwear for microelectronic industries. Recommendable in **ATEX** environments

Care and maintenance: Clean after each use and dry off away from direct heat; treat the leather with a suitable shoe-polish. Avoid contact with aggressive chemicals or extreme temperature. Avoid immersion in sea water, lime water or cement mixed with water

Recommendation: It is always necessary to wear socks made of natural fibers i.e. wool or cotton, because they provide the best performance with electrical conductivity. Avoid introducing any foreign body between foot and footbed of the footwear (i.e. insoles or similar items not equipped by the manufacturer), as they could make void the electrical properties the footwear have been conceived for. Do not undervalue the effect of ageing and contamination of the footwear: during time their electrical resistance can be subjected to alterations. It is always important to check the electrical properties of footwear through the use of special testing devices in electrostatic protected area (EPA), according to the European standard CEI EN 61340-5-1

MATERIALS / ACCESSORIES

SAFETY TECHNICAL SPECIFICATIONS

		Clause EN ISO 20345:2022 CEI EN	Description	Unit	Cofra result	Requireme nt
Complete shoe	E.S.D. features	61340-5-1	Electric resistance of footwear to floor	MΩ	85,4	< 1000
		61340-5-1	Cross resistance	MΩ	75,1	≤ 100
		61340-5-1	Charge ability	V	23,61	< 100
	Toe cap: non metallic FIBERGLASS toe cap, impact resistant until 200 J and compression resistant until 1500 kg	5.3.2.6	Shock resistance (clearance after shock)	mm	18	≥ 14
		5.3.2.7	Compression resistance (clearance after compression)	mm	14,5	≥ 14
	Anti perforation midsole: in multi-layers highly tensile fabric, penetration resistant, Zero Perforation , with low electric resistance	6.2.1.1.4	Penetration resistance (PS requirement with Ø 3,0 mm nail)	N	1313	≥ 1100
	Energy absorption system	6.2.4	Shock absorption	J	33	≥ 20
Upper	TECHSHELL , innovative, very tough, abrasion resistant, water repellent and breathable fabric, colour black/dark grey	5.4.6	Water vapour permeability	mg/cmq h	> 4,9	≥ 0,8
			Permeability coefficient	mg/cmq	> 40,4	≥ 15
		6.3	Water absorption		12,2%	≤ 30%
			Water penetration		0,02 g	≤ 0,2 g
Vamp	Textile, breathable, abrasion resistant, colour black	5.5.4	Water vapour permeability	mg/cmq h	> 84,7	≥ 2
lining	Thickness 1,2 mm		Permeability coefficient	mg/cmq	> 677,4	≥ 20
Quarter	SANY-DRY [®] , breathable, abrasion resistant, colour black	5.5.4	Water vapour permeability	mg/cmq h	> 64,4	≥ 2

lining	thickness 1,2 mm		Permeability coefficient	mg/cmq	> 515,4	≥ 20
Sole	Polyurethane/TPU made of recycled rubber granules , with low electrical resistance, directly injected in the upper:	5.8.4	Abrasion resistance (lost volume)	mm ³	102	≤ 150
	Outsole: Ice TPU, slipping resistant, abrasion resistant and hydrocarbons resistant.	5.8.5	Flexing resistance (cut increase)	mm	0,9	≤ 4
	Midsole: black polyurethane, low density, comfortable and anti-shock.	5.8.7	Interlayer bond strength	N/mm	3,7	≥ 3
		6.4.2	Hydrocarbons resistance (ΔV = volume increase)	%	2,2	≤ 12
	Adherence coefficient of the sole (Slip resistance)	5.3.5.2	ceramic + detergent solution – forepart (contact angle 7°)		0,41	≥ 0,36
			ceramic + detergent solution – heel (contact angle 7°)		0,42	≥ 0,31
		6.2.10	SR : ceramic + glycerol – forepart (contact angle 7°)		0,25	≥ 0,22
			SR : ceramic + glycerol – heel (contact angle 7°)		0,28	≥ 0,19