

G073 - INOX

Cut Protection Leather

CE CAT. 2

EN 388:2016
+A1:2018



4X43E

EN 407:2004



X2XXXX

DEXTERITY



"It is possible that gloves marked with previous standards are despatched. Cofra grants that all productions do not have technical and quality differences."

Features

- Excellent cut resistance
- Excellent softness and comfort
- Superb grip on oily and greasy surfaces

Palm

Cow split leather

Lining

Aramid yarn reinforced with a flexible steel mesh

Gauge

10

Colour

Green/neutral

Application

Mechanical industry, automotive, handling of angle grinder, handling of sharp and blunt tools

Sizes

7 (S)	8 (M)	9 (L)	10 (XL)	11 (XXL)
----------	----------	----------	------------	-------------

Lenght

24 cm	25 cm	26 cm	27 cm	28 cm
9,5"	9,9"	10,2"	10,6"	11"

Packaging

Code

Quantity

G073-D100

1 dozen (12 single packed gloves)

G073-K100

Carton containing 6 dozen (72 single packed gloves)



MULTIFUNCTIONAL FOR CUT AND HEAT



SAFETY TECHNICAL SPECIFICATIONS

The PPE is in compliance with essential requirements of (EU) 2016/425 regulation

STANDARD	DESCRIPTION	MINIMUM REQUIREMENT / RANGE	RESULT REACHED
EN 420:2003 + A1 2009	pH determination	3,5 < pH < 9,5	4,0
EN 420:2003 + A1 2009	Chromium VI determination	≤ 10 mg/kg	NOT RECORDING
UNI EN ISO 17234-1:2015	Carcinogenic and aromatic amines (leather)	≤ 30 ppm	NOT RECORDING
EN ISO 21420:2020	Further technical specifications applied	COMPLIANT / NOT COMPLIANT	COMPLIANT

STANDARD	DESCRIPTION		LEVEL					LEVEL REACHED
			1	2	3	4	5	
EN 388:2016+A1:2018	Abrasion resistance (number of frictions)		≥ 100	≥ 500	≥ 2000	≥ 8000	-	4
EN 388:2016+A1:2018	Cutting test : blade cut resistance (index)		≥ 1,2	≥ 2,5	≥ 5,0	≥ 10,0	≥ 20,0	X
EN 388:2016+A1:2018	Tear resistance (N)		≥ 10	≥ 25	≥ 50	≥ 75	-	4
EN 388:2016+A1:2018	Puncture resistance (N)		≥ 20	≥ 60	≥ 100	≥ 150	-	3
EN 388:2016+A1:2018 - EN ISO 13997	TDM : cutting resistance (N)	A	B	C	D	E	F	E
		≥ 2	≥ 5	≥ 10	≥ 15	≥ 22	≥ 30	
EN 388:2016+A1:2018 - EN 13594:2015	Impact protection	P			ABSENT			ABSENT
		Achieved			Test not executed			

If one of the marking indexes is marked with:

- letter "X" means that the test wasn't executed or not applicable;
- number "0" means that the test was executed but the minimum performance level hasn't been achieved.

STANDARD	DESCRIPTION		LEVEL				LEVEL REACHED
			1	2	3	4	
EN 407:2004 - ISO 6941	Behaviour to fire	Time persistence to flame (s)	≤ 20	≤ 10	≤ 3	≤ 2	x
		Residual glow time (s)	no requirement	≤ 120	≤ 25	≤ 5	
EN 407:2004 - EN 702	Contact Heat	Contact temperature T _c (°C)	100	250	350	500	2
		Threshold time t _t (s)	≥ 15	≥ 15	≥ 15	≥ 15	
EN 407:2004 - EN 367	Convective heat	Heat transfer index HTI (s)	≥ 4	≥ 7	≥ 10	≥ 18	x
EN 407:2004 - ISO 6942-B	Radiant heat	Heat transfer t ₂₄ (s)	≥ 7	≥ 20	≥ 50	≥ 95	x
EN 407:2004 - EN 348	Small splashes of molten metal	Number of droplets	≥ 10	≥ 15	≥ 25	≥ 35	x
EN 407:2004 - EN 373	Large splashes of molten metal	Cast iron (g)	30	60	120	200	x

If one of the marking indexes is marked with:

- letter "X" means that the test wasn't executed or not applicable;
- number "0" means that the test was executed but the minimum performance level hasn't been achieved.