

# G041 - NIMBLE

*Mechanical Protection Polyurethane*



EN 388:2016  
+A1:2018



3131X

DEXTERITY



**PU-DEX**

## Features

- Maximum dexterity and ease of movement
- Maximum lightness and breathability
- Recommended for little tools handling

## Coating

Polyurethane PU-DEX

## Lining

Nylon

## Gauge

13

## Colour

Black/black

## Application

Activities requiring superb hand dexterity, assembly, building and construction, industry, maintenance

## Sizes

6 (XS)	7 (S)	8 (M)	9 (L)	10 (XL)	11 (XXL)
--------	-------	-------	-------	---------	----------

## Lenght

21 cm	22 cm	23 cm	24 cm	25 cm	26 cm
8,3"	8,7"	9"	9,5"	9,9"	10,2"



**POLYURETHANE WITH SUPERIOR GRIP**




## Packaging

Code	Quantity
G041-D100	1 dozen (12 single packed gloves)
G041-DD00	1 dozen (1 bag containing 12 pairs)
G041-K100	Carton containing 12 dozen (144 single packed gloves)
G041-KD00	Carton containing 12 dozen (12 bags containing 12 pairs)


**PU-DEX**

New polyurethane compound that turns around the concept of grip. The excellent grasp of little tools and the maximum dexterity enhance productivity in those jobs where maximum precision and accuracy are demanded.

**PU-DEX**



**POLYURETHANE**



## SAFETY TECHNICAL SPECIFICATIONS

The PPE is in compliance with essential requirements of (EU) 2016/425 regulation

STANDARD	DESCRIPTION	MINIMUM REQUIREMENT / RANGE	RESULT REACHED
EN 420:2003 + A1 2009	pH determination	3,5 < pH < 9,5	<b>6,7</b>
UNI EN 14362-1/3:2012	Carcinogenic and aromatic amines	≤ 30 ppm	<b>&lt; 5</b>
EN ISO 21420:2020	Further technical specifications applied	COMPLIANT / NOT COMPLIANT	<b>COMPLIANT</b>

STANDARD	DESCRIPTION		LEVEL					LEVEL REACHED
			1	2	3	4	5	
EN 388:2016+A1:2018	Abrasion resistance (number of frictions)		≥ 100	≥ 500	≥ 2000	≥ 8000	-	3
EN 388:2016+A1:2018	Cutting test : blade cut resistance (index)		≥ 1,2	≥ 2,5	≥ 5,0	≥ 10,0	≥ 20,0	1
EN 388:2016+A1:2018	Tear resistance (N)		≥ 10	≥ 25	≥ 50	≥ 75	-	3
EN 388:2016+A1:2018	Puncture resistance (N)		≥ 20	≥ 60	≥ 100	≥ 150	-	1
EN 388:2016+A1:2018 - EN ISO 13997	TDM : cutting resistance (N)	A	B	C	D	E	F	X
		≥ 2	≥ 5	≥ 10	≥ 15	≥ 22	≥ 30	
EN 388:2016+A1:2018 - EN 13594:2015	Impact protection	P			ABSENT			ABSENT
		Achieved			Test not executed			

If one of the marking indexes is marked with:

- letter "X" means that the test wasn't executed or not applicable;
- number "0" means that the test was executed but the minimum performance level hasn't been achieved.