

G003 - NITRA-NEO

Mechanical Protection Nitrile



MAXIMUM VERSATILITY



Features	<ul style="list-style-type: none"> Versatile Light nitrile and oil resistant 				
Coating	Smooth nitrile				
Lining	Polyester				
Gauge	13				
Colour	Black/black				
Application	Warehouse, packaging, mechanical industry, agriculture				
Sizes	7 (S)	8 (M)	9 (L)	10 (XL)	11 (XXL)
Lenght	23 cm	24 cm	25 cm	26 cm	27 cm
	9"	9,5"	9,9"	10,2"	10,6"
Packaging	Code		Quantity		
	G003-D100		1 dozen (12 single packed gloves)		
	G003-DD00		1 dozen (1 bag containing 12 pairs)		
	G003-K100		Carton containing 20 dozen (240 single packed gloves)		
	G003-KD00		Carton containing 20 dozen (20 bags containing 12 pairs)		

SAFETY TECHNICAL SPECIFICATIONS

The PPE is in compliance with essential requirements of (EU) 2016/425 regulation

STANDARD	DESCRIPTION	RESULT REACHED
EN ISO 21420:2020	Protective gloves - General requirements and test methods	COMPLIANT

STANDARD	DESCRIPTION		LEVEL					LEVEL REACHED
			1	2	3	4	5	
EN 388:2016+A1:2018	Abrasion resistance (number of frictions)		≥ 100	≥ 500	≥ 2000	≥ 8000	-	3
EN 388:2016+A1:2018	Cutting test : blade cut resistance (index)		≥ 1,2	≥ 2,5	≥ 5,0	≥ 10,0	≥ 20,0	1
EN 388:2016+A1:2018	Tear resistance (N)		≥ 10	≥ 25	≥ 50	≥ 75	-	2
EN 388:2016+A1:2018	Puncture resistance (N)		≥ 20	≥ 60	≥ 100	≥ 150	-	2
EN 388:2016+A1:2018 - EN ISO 13997	TDM : cutting resistance (N)	A	B	C	D	E	F	X
		≥ 2	≥ 5	≥ 10	≥ 15	≥ 22	≥ 30	
EN 388:2016+A1:2018 - EN 13594:2015	Impact protection	P			ABSENT			ABSENT
		Achieved			Test not executed			

If one of the marking indexes is marked with:

- letter "X" means that the test wasn't executed or not applicable;
- number "0" means that the test was executed but the minimum performance level hasn't been achieved