

G016 - ZONAL

Mechanical Protection Nitrile



EN 388:2016
+A1:2018



4131X

DEXTERITY



Features

- The lining does not stress the hand by following its movements
- High breathability level which improves internal thermoregulation in the upper part
- Thinner fingers to grant a higher dexterity level
- Nitrile foam coating for a better compromise between protection and breathability
- Soft small cleats on the palm that considerably increase the grip on both dry and wet surfaces, making the grip even safer
- Good protection in oily environments

Coating

Nitrile foam

External finish

Nitrile small cleats on the palm

Lining

Nylon, nylon Fresh & Dry, elastane

Gauge

15

Colour

Blue-grey/black

Application

Building and construction, maintenance, material handling in the warehouse, mechanical industry, setup

Sizes

8 (M) 9 (L) 10 (XL) 11 (XXL)

Lenght

25 cm	26 cm	27 cm	28 cm
9,9"	10,2"	10,6"	11"



**EXCELLENT INTERNAL
THERMOREGULATION - COMFORT AND
HIGH DEXTERITY**



Packaging

Code

Quantity

G016-D100	1 dozen (12 single packed gloves)
G016-DD00	1 dozen (1 bag containing 12 pairs)
G016-K100	Carton containing 12 dozen (144 single packed gloves)
G016-KD00	Carton containing 12 dozen (12 bags containing 12 pairs)



**SLIP-RESISTANT
SMALL CLEATS
FOR A SAFER GRIP**

*Double zone lining, fully made of abrasion and wear resistant material, with the upper part made of ultra-thin **"FRESH & DRY"** nylon which grants higher breathability, flexibility of movements and dexterity in handling small components*



SAFETY TECHNICAL SPECIFICATIONS

The PPE is in compliance with essential requirements of (EU) 2016/425 regulation

STANDARD	DESCRIPTION	MINIMUM REQUIREMENT / RANGE	RESULT REACHED
EN 420:2003 + A1 2009	pH determination	3,5 < pH < 9,5	7,15
UNI EN 14362-1/3:2012	Carcinogenic and aromatic amines	≤ 30 ppm	NOT RECORDING
EN ISO 21420:2020	Further technical specifications applied	COMPLIANT / NOT COMPLIANT	COMPLIANT

STANDARD	DESCRIPTION		LEVEL					LEVEL REACHED
			1	2	3	4	5	
EN 388:2016+A1:2018	Abrasion resistance (number of frictions)		≥ 100	≥ 500	≥ 2000	≥ 8000	-	4
EN 388:2016+A1:2018	Cutting test : blade cut resistance (index)		≥ 1,2	≥ 2,5	≥ 5,0	≥ 10,0	≥ 20,0	1
EN 388:2016+A1:2018	Tear resistance (N)		≥ 10	≥ 25	≥ 50	≥ 75	-	3
EN 388:2016+A1:2018	Puncture resistance (N)		≥ 20	≥ 60	≥ 100	≥ 150	-	1
EN 388:2016+A1:2018 - EN ISO 13997	TDM : cutting resistance (N)	A	B	C	D	E	F	X
		≥ 2	≥ 5	≥ 10	≥ 15	≥ 22	≥ 30	
EN 388:2016+A1:2018 - EN 13594:2015	Impact protection	P			ABSENT			ABSENT
		Achieved			Test not executed			

If one of the marking indexes is marked with:

- letter "X" means that the test wasn't executed or not applicable;
- number "0" means that the test was executed but the minimum performance level hasn't been achieved