



<b>Prod. Ref.</b>	37180-N01
<b>Safety cat.</b>	S7S HI CI HRO LG SC FO SR
<b>Range of sizes</b>	40 - 48 (6,5 - 13)
<b>Weight (sz. 8)</b>	715 g
<b>Shape</b>	B
<b>Width</b>	11

**Description:** Brown water repellent Pull-Up Nubuck ankle boot, **SANY-DRY**<sup>®</sup> lining, antistatic, anti-shock, slipping resistant, non metallic **APT PLUS** midsole **Zero Perforation**

**Plus:** **METAL FREE. FOOT-PAD** footbed, extremely soft and comfortable footbed. Thanks to the very low density polyurethane, the footbed is self-molding granting a right distribution of the body weight and providing an immediate feeling of comfort. High shock absorption is provided from highly resilient material and a perfect cushion in the central area of the heel. **ANTI TORSION SUPPORT** made of polycarbonate and fibreglass conveniently placed between heel and sole, which provides support and protection of the plantar arch, thus preventing harmful bendings and/or unwilling torsion. Outsole resistant to +300°C (1 minute contact). Footwear equipped with a particularly abrasion-resistant material on the toe area (**SC**). Sole design especially conceived for safer standing on ladder rungs (**LG**). **Abrasion resistant TPU toe cap protection. Sealed seams**

**Suggested uses:** Construction, maintenance, industries

**Care and maintenance:** Clean after each use and dry off away from direct heat. Avoid contact with aggressive chemicals or extreme temperature. Avoid immersion in sea water, lime water or cement mixed with water

### MATERIALS / ACCESSORIES

### SAFETY TECHNICAL SPECIFICATIONS

		Clause EN ISO 20345:2022	Description	Unit	Cofra result	Requirement	
<b>Complete shoe</b>	<b>Water resistance</b>	5.15.1	Water resistance (area of water penetration after 1000 paces in a surface flooded with water)	cm <sup>2</sup>	≤ 3	≤ 3	
	<b>Toe cap:</b> non metallic <b>FIBERGLASS</b> toe cap, impact resistant until 200 J and compression resistant until 1500 kg	5.3.2.6	Shock resistance (clearance after shock)	mm	15	≥ 14	
		5.3.2.7	Compression resistance (clearance after compression)	mm	16	≥ 14	
	<b>Anti perforation midsole:</b> in multi-layers highly tensile fabric, penetration resistant, <b>Zero Perforation</b>	6.2.1	Penetration resistance (PS requirement with Ø 3,0 mm nail)	N	To 1100 N No perforation	≥ 1100	
	<b>Antistatic shoe:</b> the bottom is fit for the dissipation of electrostatic charges	6.2.2.2	Electric resistance				
			- wet	MΩ	93.41	≥ 0.1	
- dry		MΩ	298	≤ 1000			
<b>Heat insulation</b>	6.2.3.1	Heat insulation (temp. increase after 30' at 150 °C)	°C	7	≤ 22		
<b>Cold insulation</b>	6.2.3.2	Cold insulation (temp. decrease after 30' C at -17 °C)	°C	5	≤ 10		
<b>Energy absorption system</b>	6.2.4	Shock absorption	J	30	≥ 20		
<b>Upper</b> Brown water repellent Pull-Up Nubuck thickness 1,8/2,0 mm	5.4.6	Water vapour permeability	mg/cmq h	> 4,1	≥ 0,8		
		Permeability coefficient	mg/cmq	> 50,5	≥ 15		
	6.3	Water absorption		10%	≤ 30%		
		Water penetration		0,0 g	≤ 0,2 g		
<b>Upper</b> Black water repellent printed leather thickness 1,8/2,0 mm	5.4.6	Water vapour permeability	mg/cmq h	> 1,9	≥ 0,8		
		Permeability coefficient	mg/cmq	> 21,6	≥ 15		
	6.3	Water absorption		13,9%	≤ 30%		
		Water penetration		0,14 g	≤ 0,2 g		
<b>Vamp lining</b> Felt, breathable, colour dark grey thickness 1,2 mm	5.5.4	Water vapour permeability	mg/cmq h	> 5	≥ 2		
		Permeability coefficient	mg/cmq	> 41,9	≥ 20		
<b>Quarter lining</b> <b>SANY-DRY</b> <sup>®</sup> , breathable, abrasion resistant, colour black thickness 1,2 mm	5.5.4	Water vapour permeability	mg/cmq h	> 64,4	≥ 2		
		Permeability coefficient	mg/cmq	> 515,4	≥ 20		

Sole						
	Polyurethane/Nitrile rubber, antistatic, directly injected in the upper:	5.8.4	Abrasion resistance (lost volume)	mm <sup>3</sup>	<b>112</b>	≤ 150
	Outsole: black nitrile rubber, slipping resistant, abrasion resistant, hydrocarbons resistant and heat resistant.	5.8.5	Flexing resistance (cut increase)	mm	<b>2</b>	≤ 4
	Midsole: dark grey polyurethane low density, comfortable and anti-shock	5.8.7	Interlayer bond strength	N/m	<b>4,2</b>	≥ 3
		6.4.4	Hot resistance (300 °C)	----	<b>any melting</b>	any melting
		6.4.2	Hydrocarbons resistance ( $\Delta V$ = volume increase)	%	<b>10</b>	≤ 12
Adherence coefficient of the sole (Slip resistance)		5.3.5.2	ceramic + detergent solution – forepart (contact angle 7°)		<b>0,40</b>	≥ 0,36
			ceramic + detergent solution – heel (contact angle 7°)		<b>0,35</b>	≥ 0,31
		6.2.10	SR : ceramic + glycerol – forepart (contact angle 7°)		<b>0,27</b>	≥ 0,22
			SR : ceramic + glycerol – heel (contact angle 7°)		<b>0,32</b>	≥ 0,19